



# MTU Diesel Generator Set

*Power System Engineer*



## ZBM3025



### Performance

- Carefully selected components
- Accurately developed and tested configuration

### Quality Control

- International standard testing procedure
- Professional manufacture team

### Service efficiency

- Humanization design and improvements
- Superior accessibility to all service points

### Increased transport efficiency

- Compact and safe concept
- Sturdy design

### Superior resale value

- Designed and built to last



[www.zpimachinery.com](http://www.zpimachinery.com)

All specification can be changed without notice.

# Technical Data

Model	ZBM3025	
Prime power	kw/kva	2200/2750
Standby power	kw/kva	2420/3025
Rated speed	r/min	1800
Standard Voltage	V	480
Available Voltages	V	480/277-440/254-220/127-208/120
Rated power factor		0.8

Engine	CONTINUOUS	STANDBY	
Rated Output	kW	2490	2730
Manufacturer	MTU		
Model	20V4000G43		
No. of Cylinders and Build	4 Cycle;12V Cylinder Diesel		
Aspiration and Cooling	Exhaust turbo charger and Air charge air cooling;		
Bore/Stroke	mm	170X210	
Compress the ratio	16.5:1		
Cooling system	Water-cooled		
Engine Speed/Frequency	rpm/Hz	1800/60HZ	
Coolant Capacity	L	795	
Starting System	Electric 24 volt DC		
Displacement	L	95.4	
Lubricant system Capacity	L	390	
Battery Volatge / Capacity	24VDC		
Governing Type	Type	Electronic engine management system "ADEC"	
Air Filter	Type	Dry	
Fuel Consumption	Load	100% 75% 50% 25%	
	L/h	615 476 332 192	

ALTERNATOR BRAND	LEROY SOMER	STAMFORD
Model	PI734G	
Exciter System	Self-excited, brushless	
Poles	Num	4
Cooling Fan	Cast alloy aluminum	
Bearing	Single,double shielded	
Windings	100% copper	
Connection Type	Reconnectable	
Insulation Type	Class	Class H
Pitch	2/3	
Amortisseur Winding	Full	
Voltage Regulator	A.V.R. (Electronic)	
Steady Voltage Precision	± 1%	
Underspeed Protection	Standard	
Overexcitation Protection	IP23	
TIF (1960 Weightings)	<50	

Dimension		
Length*width*height	mm	6100*2700*2800
Net weight	kg	18000

## Control Panel- SMARTGEN 6110/6120

The base mounted control panel in a vibration isolated sheet steel enclosure. The control panel is equipped as follows:

- Instruments: Analogue Voltmeter, Hours Run Meter, Water pressure Meter.
- Controls: Emergency Stop Pushbutton, Voltmeter Phase Selector Switch.
- Control module: Standard collocation is smartgen Auto start with AMF.



### Main Features:

- Δ Automatic mains failure
- Δ Engine control, Generator protection
- Δ Built in alarms and warnings
- Δ Remote Start operation available
- Δ Fuel pump control
- Δ Mains simulation
- Δ Block heater control
- Δ Field adjustable parameters
- Δ Free MS-Windows Remote monitoring
- Δ LED displays
- Δ Configurable analogue inputs
- Δ I/O expansion capability

### Protection Circuits

- WARNING
- Battery charge failure
- Low battery voltage
- SHUT DOWNS
- Fail to start
- Emergency stop
- Low oil pressure
- High engine temperature
- Over /Under speed
- Under/over generator frequency
- Failed to reach loading voltage
- Electrical trip
- Generator over current

### Instruments

- ENGINE
- Engine speed
- Oil pressure
- Coolant temperature
- Run time
- Battery volts
- TOR
- Voltage (L-N)
- Current (L1-L2-L3)
- Frequency
- Mains
- Voltage (L-L, L-N)



This generator does comply with EU requirements related to working environment, regulations concerning safety and emissions as well with the outdoor noise directive 2000/14/EC.